

Utensil washer LU-130 400/50/3N



- Stainless steel construction.
- Counterbalance split door, with double-skinned lower section.
- Stainless steel extractable tray.
- Insulated double skinned tank with sloped bottom and large diameter connections, to avoid deposit of residues. Wash area with no "shadow" zones.
- Stainless steel pump housings and impellers. The pumps are installed vertically and are self-draining.
- Stainless steel wash and rinse arms.
- Adjustable, extra-high feet (200-250mm).
- Complete with rinse boiler.
- Boiler and tank heating elements in Incoloy 800.
- Front location of all electrical components, wash pumps and hydraulic connections, for easy access.
- This machine has been designed and manufactured in accordance with the specifications laid down in European directives 89/392/EEC and 73/23/EEC.
- Please note: as a result of continuous product improvements, these specifications are subject to change without prior notice

:
 Basket dimensions (mm.): 1.350 x 700
 No. of baskets : 1 cesto inox, 1 suplemento 4 bandejas
 Usable height (mm.): 680
 :
 Booster pump (kW): 0.37
 Electrical loading:
 Wash pump (kW): 2.2 + 2.2
 Wash tank (kW): 9.8
 Boiler (kW): 19.6
 Total power (kW): 24
 :
 Water supply temperature (°C): 10-60
 : 10-60
 : 10-90
 Water capacity:
 Wash tank (l.):
 Boiler (l.):
 Water consumption (l.):
 Cycle (2 bar pressure): 14
 External dimensions (mm.):
 Width: 1.520
 Depth (open / closed): 1.235 / 890
 Height (open / closed): 2.080 / 1.760
 Net weight (Kg.): 220
 ELECTRICAL SUPPLY: 400V / 50 Hz / 3N~