

Utensil washer LU-61H 400/50/3N



- Stainless steel construction.
- Counterbalance split door, with double-skinned lower section.
- Stainless steel extractable tray.
- Integral double-skinned insulation. Stretch formed tank.
- Stainless steel pump housing and impeller.
- Stainless steel wash and rinse arms.
- Adjustable, extra-high feet (200-250mm).
- Complete with rinse boiler.
- Boiler and tank heating elements in Incoloy 800.
- Front location of all electrical components, wash pump and hydraulic connections, for easy access.
- This machine has been designed and manufactured in accordance with the specifications laid down in European directives 89/392/EEC and 73/23/EEC.
- Please note: as a result of continuous product improvements, these specifications are subject to change without prior notice

:
 Basket dimensions (mm.): 630 x 550
 No. of baskets : 1 cesto inox, 1 suplemento 4 bandejas
 Usable height (mm.): 820
 :
 Booster pump (kW): 0.37
 Electrical loading:
 Wash pump (kW): 3
 Wash tank (kW): 5.3
 Boiler (kW): 8.3
 Total power (kW): 11.2
 :
 Water supply temperature (°C): 10-60
 : 10-60
 : 10-90
 Water capacity:
 Wash tank (l.):
 Boiler (l.):
 Water consumption (l.):
 Cycle (2 bar pressure): 7
 External dimensions (mm.):
 Width: 675
 Depth (open / closed): 1.150 / 803
 Height (open / closed): 2.200 / 2.015
 Net weight (Kg.): 150
 ELECTRICAL SUPPLY: 400V / 50 Hz / 3N~